

Section 1 - Product Name

Product Name: Bonded Injection Molded Samarium Cobalt Magnet

Section 2 - Hazardous Ingredients

Chemical Name: Bonded Injection Molded Samarium Cobalt Magnet

Material/Component(s):

Material or	Weight %	CAS No.	ACGUH TLV (mg/m^3)	Notes
Component				

Section 3 - Physical Characteristics

Vapor Pressure: N/A Vapor Density: N/A Specific Gravity: 6.6 Melting Point: 215-225° C Evaporation Rate: N/A

Odor: N/A

Solubility in Water: Insoluble

Section 4 - Fire and Explosion Hazard Data

Flash Point: N/A

FLAMMABLE LIMITS: N/A

LEL: N/A UEL: N/A

Extinguishing Media: Dry sand or special powder extinguisher

Special Fire Fighting Procedures: Use a special powder extinguisher, or pour dry sand on the fire to

cut off the oxygen supply. Water should be avaoided at all costs.

Unusual Fire and Explosion Hazards(s): Flammable

Section 5 - Reactivity Data

Stability: Stable

Conditions to Avoid: No known incompatibilities Incompatibility (Materials to Avoid): N/A



Hazardous Polymerization: Will not occur Hazardous Decomposition or Byproducts: N/A

Section 6 - Health Hazard Data

Health Hazards (Acute & Chronic): Allergic skin irritations can occur on contact . Harmful if inhaled -- Irritation of mucous membranes and epithelium of the respiratory organs. Dermal immune response may occur as result of repeated or long term exposure.

Emergency and First Aid Procedures:

Procedure For	Procedure
---------------	-----------

Section 7 - Precautions for Safe Handling and Use

Spill Procedure: Not a hazard as a solid compact magnet. Use protective gear. Place spillage into metal can and store in preparation for disposal.

Waste Disposal Method: Observe all federal, state, and local regulations when disposing this material.

Section 8 - Control Measures

Respiratory Protection: N/A
Eye Protection: Safety goggles
Skin Protection: Protective Gloves
Ventilation: Mechanical (General)
Work / Hygienic Practices: N/A

Address: 3100 Cascade Drive, Valparaiso, IN 46383 USA, Telephone: (219) 465-1998, Fax: (219) 462-5146